



**PERFORMANCE CURVE**

**Models:**  
**HE16W20**  
**PE16W20**  
**SE16W/S16W**  
**V16W**

Back-Pull-Out Casing  
**5-Blade Impeller**  
**16" Discharge**  
**20" Suction**

CURVE	POWER (HP/KW)	SPEED (RPM)	IMPELLER DIAMETER
A	250/185	890	21.00" (533 mm)
B	200/150	850	21.00" (533 mm)
C	200/150	800	21.00" (533 mm)
D	150/110	775	21.00" (533 mm)
E	150/110	740	21.00" (533 mm)
F	125 / 90	720	21.00" (533 mm)
G	100 / 75	675	21.00" (533 mm)
H	75 / 55	600	21.00" (533 mm)
I	40 / 30	500	21.00" (533 mm)
J	20 / 15	400	21.00" (533 mm)

DO NOT OPERATE PUMP IN DOTTED PORTION OF CURVES. PUMPS MAY EXCEED HP SHOWN IF OPERATED IN DOTTED PORTION OF CURVE. CURVES ARE SUBJECT TO CHANGE WITHOUT NOTICE. EFFICIENCIES SHOWN ARE NOMINAL BOWL. GUARANTEED MINIMUM EFFICIENCIES PER H.I. LEVEL A.

