

PERFORMANCE CURVE

Models:
HE3M6
PE3M6
SE3M

CURVE	POWER (HP/KW)	SPEED (RPM)	IMPELLER DIAMETER
A	40 / 30	2900	8.00" (203 mm)
B	30 / 22	2750	8.00" (203 mm)
C	25 / 19	2550	8.00" (203 mm)
D	15 / 11	2100	8.00" (203 mm)
E	15 / 11	1900	8.00" (203 mm)
F	10 / 7.5	1765	8.00" (203 mm)
G	7.5 / 5.5	1600	8.00" (203 mm)
H	7.5 / 5.5	1460	8.00" (203 mm)
I	5 / 4	1300	8.00" (203 mm)
J	5 / 4	1170	8.00" (203 mm)

Back-Pull-Out Casing
5-Blade Impeller
3" Discharge
6" Suction

DO NOT OPERATE PUMP IN DOTTED PORTION OF CURVES. PUMPS MAY EXCEED HP SHOWN IF OPERATED IN DOTTED PORTION OF CURVE. CURVES ARE SUBJECT TO CHANGE WITHOUT NOTICE. EFFICIENCIES SHOWN ARE NOMINAL BOWL. GUARANTEED MINIMUM EFFICIENCIES PER H.I. LEVEL A.

