

PERFORMANCE CURVE

Models:
HE6W
PE6W
SE6W

Back-Pull-Out Casing
4-Blade Impeller
6" Discharge
8" Suction

CURVE	POWER (HP/KW)	SPEED (RPM)	IMPELLER DIAMETER
A	100 / 75	1785	11.80" (300 mm)
B	75 / 55	1725	11.80" (300 mm)
C	60 / 45	1600	11.80" (300 mm)
D	50 / 37	1460	11.80" (300 mm)
E	40 / 30	1400	11.80" (300 mm)
F	30 / 22	1250	11.80" (300 mm)
G	25 / 18.5	1180	11.80" (300 mm)
H	20 / 15	1100	11.80" (300 mm)
I	15 / 11	970	11.80" (300 mm)
J	10 / 7.5	885	11.80" (300 mm)
K	7.5 / 5.5	775	11.80" (300 mm)
L	5 / 4	690	11.80" (300 mm)
M	5 / 4	500	11.80" (300 mm)

DO NOT OPERATE PUMP IN DOTTED PORTION OF CURVES. PUMPS MAY EXCEED HP SHOWN IF OPERATED IN DOTTED PORTION OF CURVE. CURVES ARE SUBJECT TO CHANGE WITHOUT NOTICE. EFFICIENCIES SHOWN ARE NOMINAL BOWL. GUARANTEED MINIMUM EFFICIENCIES PER H.I. LEVEL A.

