

PERFORMANCE CURVE

Models:
HE8L10
PE8L10
S8L
V8L

Back-Pull-Out Casing
4-Blade Impeller
8" Discharge
10" Suction
 Variable Speed Curve

CURVE	POWER (HP/KW)	SPEED (RPM)	IMPELLER DIAMETER
A	150 / 110	1785	13.50" (343 mm)
B	125 / 90	1700	13.50" (343 mm)
C	100 / 75	1600	13.50" (343 mm)
D	75 / 55	1460	13.50" (343 mm)
E	60 / 45	1350	13.50" (343 mm)
F	50 / 37	1275	13.50" (343 mm)
G	40 / 30	1180	13.50" (343 mm)
H	30 / 22	1050	13.50" (343 mm)
I	25 / 18.5	970	13.50" (343 mm)
J	20 / 15	880	13.50" (343 mm)

DO NOT OPERATE PUMP IN DOTTED PORTION OF CURVES. PUMPS MAY EXCEED HP SHOWN IF OPERATED IN DOTTED PORTION OF CURVE. CURVES ARE SUBJECT TO CHANGE WITHOUT NOTICE. EFFICIENCIES SHOWN ARE NOMINAL BOWL. GUARANTEED MINIMUM EFFICIENCIES PER H.I. LEVEL A.

