

---

## VAUGHAN COMPANY OFF LOADING AND LONG-TERM STORAGE INSTRUCTIONS NOZZLE

---

### **OFF LOADING AND INSPECTION INSTRUCTIONS:**

Prior to shipment Vaughan pumps are carefully crated and inspected to ensure arrival at your site in good condition. On receiving your nozzles, examine it carefully to assure that no damaged crating or broken parts have resulted from mishandling during shipping. Look for signs that the nozzle has been dropped, such as missing paint, dents, or cracks. If damage has occurred, report to your carrier immediately, and consult your local Vaughan representative or call Vaughan Co. for advice. Be sure to remove the flange cover at time of installation.

OFFLOADING	CONFIRMATION	NAME & DATE
Receipt inspection notes no damage?	Yes___ No___	

### **STORAGE REQUIREMENTS TO BE UNDERTAKEN BY CONTRACTOR:**

Both the epoxy paint and the Victaulic clamp gaskets on the nozzle assembly are susceptible to damage from prolonged UV exposure. If nozzle assemblies are to be stored for more than two weeks prior to installation, they must be either stored indoors or tarped. If nozzle assemblies will be exposed to sunlight for more than two weeks after installation, they should be tarped.

STORAGE	CONFIRMATION	NAME & DATE
Nozzles are stored indoors?	Yes___ No___	
Are nozzles tarped?	Yes___ No___	

*All storage & maintenance log records must be retained and made available to the factory upon request.*